



FOR MIXING OR DIVERTING
 3-WAY ACTING
 316SS BODY MATERIAL
 316SS TRIM MATERIAL
 THREADED CONNECTION

VALVE BODY NUMBER	SIZE		CAPACITY (CV)	MAXIMUM CLOSE-OFF PRESSURE psid (bar)	DIMENSIONS IN (MM)			APPROXIMATE SHIPPING WT. lbs (kg)
	CONNECTION (NPT)	NOMINAL PORT			A	B	C	
300WA42	1/2"	1/2"	6	300 (20.7)				7.5 (3.41)
301WA42	3/4"	3/4"	8	300 (20.7)	4-29/32 [124.62]	2-29/32 [73.82]	3-13/32 [86.52]	7.5 (3.41)
302WA42	1"	1"	11	300 (20.7)				7.5 (3.41)
304WA42	1-1/2"	1-1/2"	20	200 (13.8)	6-7/64 [155.18]	3-13/32 [86.52]	4 [101.6]	15 (6.82)
305WA42	2"	2"	30	100 (6.9)	6-1/2 [165.1]	3-13/16 [96.84]	4-13/64 [106.76]	18.5 (8.41)

SCALE 1:2

Ⓒ = CRITICAL DIMENSION
 STANDARD TOLERANCES UNLESS NOTED:
 ALL DECIMAL DIMENSIONS ± .005
 ALL ANGLES ± 1°

NO.		CHANGES		DATE		NAME		MATERIAL	
				DWN BY		38R SERIES		FINISH	
				CHKD		3-WAY STAINLESS STEEL		Dwyer Instruments, Inc.	
				APPD		VALVE BODY		MICHIGAN CITY, INDIANA 46360 U.S.A.	
				BY/DATE		ACAD2002		FR. NO.	
						3			

NOTICE: This drawing and the principles and elements of design embodied therein are the exclusive property of DWYER INSTRUMENTS, INC. and are not to be communicated, disclosed, reproduced or used except as previously authorized in writing by such corporation and must not be submitted to outside parties for examination without the written consent of said corporation.